

Service Bulletin

Char-Lynn®
Hydraulic Motors

No. S92112
November 12, 1992



Date: November 12, 1992

Subject: Torx Head Cap Screw Change in A, H, R & S Motors

Effective April 5, 1993, the following changes will be made to the A, H, R & S Char-Lynn Motors:

- Mounting flange retaining screws change from 12 point cap screws (part no. 5777) to external Torx head cap screws (part no. 16292-088).
- End Cap retaining cap screws change from 12 point cap screws (5389 Series) to Torx head cap screws with/sealant (16294 Series). Since the new capscrews will have a sealant under the head, we will eliminate the 14488 washer. The washer will continue to be furnished in the seal kits for service.

Torx head cap screws have a much stronger head to resist tool stripping and they have a flatter surface under the head for a better seal. The new cap screws use driver size E-10, available at tool supply houses. The cap screw installation torque will remain the same as published in the repair manuals. The 12 point cap screws will no longer be available as service parts after the April change over date, and will be replaced by Torx head cap screws.

Willard Bennett
Technical Services Manager

Eaton Corporation
Hydraulics Division
15151 Hwy. 5
Eden Prairie, MN 55344
Telephone 612/937-9800
Fax 612/937-7130

Eaton Ltd.
Hydraulics Division
Glenrothes, Fife
Scotland, KY7 4NW
Telephone 01-592-771-771
Fax 01-592-773-184

Eaton GmbH
Hydraulics Products
Am Schimmersfeld 7
40880 Ratingen, Germany
Telephone 02102-406-830
Fax 02102-406-800



Quality System Certified
Products in this catalog are manufactured
in an ISO-9001-certified site.

EAT•N